

Data Sheet for Precision Potentiometer

Conductive Plastic Hollow Shaft Potentiometer

Series MHP16



- Miniaturized precision potentiometer for very thin shafts ($\varnothing 2$ mm)
- Simple mounting due to flattened hollow shaft and flange
- Conductive plastic and high-quality multi finger wiper (precious metals) gives a reliable signal output

The conductive plastic hollow shaft potentiometer MHP16 offers easy mounting and exact zero point alignment thanks to its flattened hollow shaft and flange. The very compact design allows the use in very limited space conditions.

Electrical Data

Effective electrical angle of rotation 1.)	320° $\pm 5^\circ$
Total resistance 1.)	1 kOhm
Resistance tolerance	$\pm 20\%$
Independent linearity (best straight line) 1.)	$\pm 2\%$
Theoretical resolution 1.)	Nearly infinite
Max. / recommended wiper current 1.)	10 μA / 1 μA
Power rating @ 70°C (0W @ 105°C)	0,5 W
Insulation Voltage 1.)	500 VAC, 1min
Insulation Resistance 1.)	500 MOhm @ 500 VDC

Mechanical Data, Environmental Conditions, Miscellaneous

Mechanical angle of rotation	360° without stop
Lifetime (90% el. eff. angle half sine) 2.)	2 Mio. rotations
Max. operational speed	90 rev. / min.
Bearing	Sleeve bearing
Operational torque @ ambient temperature 1.) 2.)	7 Nmm
Operating temperature range	-40..+105°C
Storage temperature range	-40..+105°C
Protection grade (IEC 60529)	IP40
Housing diameter	16,4 mm
Housing depth	6 mm
Shaft diameter	2 mm
Shaft type	Hollow shaft
Connection type	Gold plated solder pad
Connection position	Radial
Sensor mounting	Flange
Mass	2 g
Material hollow shaft hub	Plastic
Material housing	Plastic

1.) According IEC 60393

2.) Determined by climatic conditions according to IEC 68-1, para. 5.3.1 without load collectives

Please note: Max. permissible supply voltage <75 VDC respectively <50 VAC in addition the max. power rating must be observed

Data Sheet for Precision Potentiometer

Conductive Plastic Hollow Shaft Potentiometer

Series MHP16

Order code

Description	Selection: standard=black/bold, possible options=grey/cursive			
Series	MHP16			
Resistance value: 1 kOhm		R1k		
Resistance tolerance: ±20%			W20%	
Independent linearity: ±2%				L2%

For higher quantities or on-going demand, additional options are available as described below

For example:

- Other electrical rotation angles or resistance values
- Special tolerances of independent linearity
- Custom specific housings

Data Sheet for Precision Potentiometer



Conductive Plastic Hollow Shaft Potentiometer

Series MHP16

Drawing

