

BX25 Ex2/22 Weighing Terminal

ATEX and IECEx certified for usage in Zones 2/22

Main Features

- Multi-language operator prompts
- Color changing display, SmartAPP & 16 digit alphanumeric info line.
- User programmable 3 keys and 2 touch free keys for applications.
- 2 platform connections & total scale
- Data entry via barcode reader.
- Stainless steel, IP67 protected for wet, hygienic and harsh areas.

High Technology & Performance

- Up to 999 999 display resolution.
- Up to 1600 conversions per second.
- Application based SmartAPP for easy human machine interface.
- High capacity tank scales supported by eCAL- electronic calibration & span correction at non-empty tanks.

SmartAPP Applications

- Weighing and data collection.
- Customized labelling with barcode
- Classification, checkweighing, packing and filling.
- Piece counting.
- Vertical or Horizontal Totalization.
- Livestock and dynamic weighing.

6 Memories, Each with 500 Items

- 2 pcs ID1 & ID2 memory.
- Item limits memory for applications.
- Preset tare memory.
- Average piece weight memory at piece counting.
- Automatic linkage between memories.

Integration & Connectivity

- Zone 2/22 Certified interfaces;
- 2 x RS232C, 1 x RS485.
 - Ethernet TCP/IP,
 - Profibus, Profinet, EtherNet/IP, EtherCAT, CC-Link, Powerlink,
 - Analogue output and Digital I/O.



BX25 Ex2/22 is ATEX and IECEx certified weighing terminal, which offers high accuracy and performance in the hazardous areas with strong connectivity options.

This weighing terminal is programmable for basic weighing, labelling, packing, checkweighing, classifying, filling, piece counting and dynamic weighing applications. Five user programmable keys including two touch free keys provide practical and error free operation. This instrument has 6 pcs memories; ID1, ID2, preset tare, APW, item limit values; each have 500 records capacity.

BX25 EX2/22 offers various interfaces for seamless integration with PC or PLC for transactional or process weighing applications. Additionally, Analogue output, and programmable Digital 4 inputs and 5 outputs are available to control the external equipment.

Typical Applications in Hazardous Area

1. Industrial Process control and Weighing Applications

Its SmartAPP weighing applications and integration features including Fieldbus interfaces.

2. Labelling & Data Collecting

BX25 Ex2/22 can print different type of standard tickets including totalizing and customized tickets with barcode.

3. Piece Counting

Counting can be done by sampling or average piece weight is saved from APW memory. 500 items memory capacity for piece weights.

4. Automatic / Manual Packing

Most common usage of this mode is manual packing of agricultural products. 500 items memory for sets of limits.

5. Automatic / Manual Checkweighing

The weight or the quantity of the items in the package on the scale is controlled. 500 items memory for sets of limits.

6. Automatic / Manual Classifying

Products can be classified according to the weight or quantity of item in the package. 500 items memory for sets of limits.

7. Automatic / Manual Gravimetric Filling

Automatic / manual filling can be executed in gross mode or in net mode. 500 items memory for sets of limits.

8. Data Entry Via Barcode, RFID Reader

Direct connection of barcode reader or RFID reader to enter IDs, PT.

9. Statistical report

Statistical report has total, average, statistical deviation, relative statistical deviation, min, max and range data.

Baykon A.S.
www.baykon.com
Istanbul, Turkey

23.02.2017
09:16
CN 34

OPERATOR
JOSEPH SMITH

MATERIAL
ASCORBIC ASID

G 4.772 kg
T 1.675 kg
N 3.097 kg

* Thank you *

Baykon INC
www.baykon.com


Date 23.02.2016
Time 09:24
CN 54

OPERATOR
JOSEPH SMITH


MATERIAL
POLYETHYLENE

Tare 0.201 kg
1 Net 0.599 kg
2 Net 0.604 kg
3 Net 0.600 kg

TOTAL
Gross 1.803 kg
Tare 0.201 kg
Net 1.602 kg
Ave 0.602 kg
SD 0.003 kg
Srel 0.2%
Min 0.599 kg
Max 0.604 kg
Range 0.005 kg



Technical Specifications

| | | |
|-----------------------------------|--|--|
| Accuracy class & EU type approval | OIML class III, single range, up to three range multi range or multi interval. | |
| Display | Wide angle LCD display with multicolor backlight, 6 digits 22 mm in height weight display and 16 digits 8 mm in height alphanumeric information display. | |
| Resolution | Display resolution is up to 999 999 and internal resolution is up to 16 000 000 counts. | |
| A/D conversion | Up to 1600 conversion rate, 24 bit Delta-Sigma ADC, 0.4 µV/d (legal metrology), 0.05 µV/d (industrial). | |
| Analogue input range | -5 mV to +19 mV | |
| Calibration technics | Standard calibration test with test weights, multipoint calibration, eCAL, electronic calibration without test weight, span adjustment of non-empty tanks. | |
| Digital filter | 5 step adjustable digital adaptive filter and 5 programmable digital dynamic filter. | |
| Functions | 2 x ID data, ticket number, date & time, total indication, Header definitions for IDs as customer, material, quality, color...etc. | |
| Standard applications | Labelling, checkweighing, classifying, packing, filling, piece counting, totalization of the sequential weighing, totalization of the additive items, livestock weighing. SD card slot for data logging. | |
| Memory | ID1 and ID2 memories, specific tare memory, item limit values memory for basic weighing and applications, average piece weight memory for piece counting. Each memory record size is 500 items. | |
| Programmable keys | 3 function keys and 2 touch free keys. | |
| Digital inputs and outputs | Programmable, opto isolated 4 inputs, and 5 relay contact outputs. Application specified In / Out functions at SmartAPP | |
| Data output | Galvanically isolated, 2 pcs RS232C and RS485 (Modbus RTU), Ethernet TCP/IP (Modbus TCP) and micro USB. | |
| Number of load cells | Up to 8 load cells 350 Ω or up to 24 load cells 1200 Ω (min. 43 Ω). | |
| Hazardous Area |  ATEX Approval II 3G Ex ic ec [ic] IIC T6 (Gases) II 3D Ex ic tc [ic] IIIC T85°C IP67 (Dust) | IECEx Approval Gases Ex ic ec [ic] IIC T6 Gc Dust Ex ic tc [ic] IIIC T85°C Dc IP67 |
| Operation temperature | -15°C ~ +55°C max. (Operational), -10°C ~ +40°C (Legal metrology and Hazardous area). | |
| Humidity | Max. 90 % non condensing relative humidity. Legal metrology max. 80 % RH. | |
| Alibi memory | 99 999 weighing record size. | |
| Housing and protection class | Desktop and wall type stainless steel, IP67 protected. | |
| Power source | 100 - 240 VAC, 50/60 Hz or 12 - 28 VDC for power supply in Ex area or for external Battery. | |
| Options | | |
| Scale options | Second analogue scale input, Alibi memory. | |
| Interfaces | Opto isolated digital 4 inputs / 5 relay contact outputs, Analogue output, Profibus, Profinet, EtherNet/IP, EtherCAT, CC-Link, Powerlink. | |
| Accessories | Ex-proof Battery pack, Ex-proof Junction box, Ex-proof load cell cable, data cable Column mount kit, Wall mount kit, 2D Wall mount kit. | |